Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
LI	3523	438/184,230,265,303,595,689.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 15:33
L2	239	1 and (semiconductor near memory)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:44
L3	5	2 and (spac\$3 near distance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:08
L4	181	2 and (spac\$3 distance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:11
L5	89	4 and (line near (pattern\$1 metal bit conduct\$3))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:07
L6	1	2 and (ratio with (spac\$3 distance) with width)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:04
L7	444735	"257"/\$.ccls. "438"/\$.ccls. "365"/\$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:03
L8	36032	7 and (semiconductor near memory)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:32

L9	0	8 and (ratio with (width near2 (line near (metal\$1 pattern\$1conduct\$3 wir\$3)) with (spac\$3 distance)))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:05
L10	308	8 and ((line near (pattern\$1 metal bit conduct\$3)) with (peripheral near2 (region\$1 area\$1)))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:07
L11	5	10 and (spac\$3 near distance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:11
L12	132	10 and ratio	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:04
L13	107	12 and (spac\$3 distance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ОИ	2005/03/24 16:41
L14	566	(spac\$3 distance length) near2 between near2 (line near (pattern metal conduct\$3 wir\$3 bit)) with width	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:03
L15	95	14 and (semiconductor near memory)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 16:44
L16	244	(spac\$3 distance length) near2 between near2 (line near (pattern metal conduct\$3 wir\$3 bit)) near2 width	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:30
L17	100	16 and ratio	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:32

L18	7	("5858869" "5939771" "6034418" "6046502" "6060382" "6268657" "6355983").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 17:12
L19	13	("5436412" "5468685" "5514908" "5656543" "5666007" "5682062" "5691280" "5691572" "5712768" "5883433" "6027995" "6037664" "6147402").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 17:18
L20	21	("4618541" "5079600" "5116459" "5177588" "5186745" "5219669" "5407866" "5453642" "5549786" "5578226" "5594080" "5641712" "5665657" "5767014" "5783481" "5792705" "5883219" "5886410" "5889330" "5923074" "5924005").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 17:27
L21	10	ratio with "1:1.05" with "1:1.30"	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 17:28
L22	2997	(spac\$3 distance length) near2 between near2 (line near (pattern metal conduct\$3 wir\$3 bit))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:31
L23	7057	width near2 (line near (pattern metal conduct\$3 wir\$3 bit))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:31
L24	757	22 and 23	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:31
L25	381	24 and ratio	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:32
L26	84	25 and (semiconductor near memory)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/24 17:32
L27	19	("4944836" "5262354" "5330883" "5354706" "5422516" "5602423" "5635423" "5663076" "5693568" "5708303" "5736457" "5753967" "5789818" "5801904" "5905307" "5949143" "5998814" "6060176" "6066896").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 17:38

L28	19	("4944836" "5262354" "5330883"	US-PGPUB;	OR	ON	2005/03/24 17:42
.		"5354706" "5422516" "5602423"	USPAT;			
		"5635423" "5663076" "5693568"	USOCR			
		"5708303" "5736457" "5753967"				
		"5789818" "5801904" "5905307"				
		"5949143" "5998814" "6060176"				
		"6066896").PN.				